

Tel.: +86 20 39388220

Web: <http://www.rhaudiopa.com/>

Fax: +86 20 31072811

Email: [info@rh-audio.net](mailto:info@rh-audio.net)

## PA System Pendant Speaker RH-SL01



The [RH-AUDIO](#) Pendant Speaker RH-SL01 is designed for use where traditional ceiling mounted speakers are difficult or impractical to install, providing coverage angles of 360 degrees horizontal and 140~160 degrees vertical, giving an even dispersion over the audio spectrum.

This excellent dispersion together with smooth frequency response and carefully controlled performance enable this speaker to offer solutions to many problems that arise in difficult acoustic applications.

Built-in transformers which suit both 70V and 100V high-voltage audio distribution systems, are easily secured and installed through the hook with a steel wiring 2 meters, which can be cut to a length required according to actual application.

Is used commonly in such areas as very high raked, suspended, concrete, or exposed ceilings etc.

The characteristics of [pendant speakers 70v](#):

- ※ Speaker driver: full range 5"×1.
- ※ With rated power 10W.
- ※ Built-in 100V transformer (This technique of line input 100V reduces signal losses on a longer distance and allows easy parallel connection of multiple loudspeakers).
- ※ Wiring length 2 meters.



Guangzhou Xinghongde Electronics Technology Co., Ltd.

Tel.: +86 20 39388220

Web: <http://www.rhaudiopa.com/>

Fax: +86 20 31072811

Email: [info@rh-audio.net](mailto:info@rh-audio.net)

The specifications of [community pendant speakers](#):

Model	RH-SL18
Rated Power	10W
Input Voltage	100V
Frequency Response	130Hz-15KHz
Sensitivity(1w,1n)	92±3 dB
Dimension	Φ138*205mm
Finished	White
Material	Alloy
Speaker Unit	Full range5"*1
Net Weight	2.0 kg

